

PA 1095166

1B04/51417

US030262

REC'D 12 AUG 2004

AWIPA PAT

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

November 19, 2003

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 60/494,135

FILING DATE: August 11, 2003

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS



M. K. Hawkins
M. K. HAWKINS
Certifying Officer

Please type a plus sign (+) inside this box → +

PTO/SB/16 (02-01)
Approved for use through 10/31/2002. OMB 0851-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C., 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Alexandria, VA 22313-1450

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53 (c).

Express Mail Label No. EV312 069 848 45 Date of Deposit: August 11, 2003

INVENTOR(S)		
Given Name (first and middle [if any])	Family Name or Surname	Residence (City and either State or Foreign Country)
George Giang Truong Jack Kyriakos	Marmaropoulos Vu Mama	Yorktown Heights, NY Ossining, NY London England, GB

☐ Additional inventors are being named on the _____ separately numbered sheets attached hereto

TITLE OF THE INVENTION (280 characters max)

MAGNETIC ELECTRICAL INTERCONNECT

CORRESPONDENCE ADDRESS

Direct all correspondence to:

☒ Customer Number

24737

24737

OR

Type Customer Number here

☒

Firm or
Individual Name

PHILIPS INTELLECTUAL PROPERTY & STANDARDS

Address

345 SCARBOROUGH ROAD

Address

P.O. Box 3001

City

BRIARCLIFF MANOR

State

NY

ZIP

10510-8001

Country

USA

Telephone

(914) 333-9608

Fax

(914) 332-0615

ENCLOSED APPLICATION PARTS (check all that apply)

☒ Specification Number of Pages

18

☐ CD(s), Number

☒ Drawing(s) Number of Sheets

9

☐ Other (specify)

☐ Application Data Sheet. See 37 CFR 1.76

METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT (check one)

☐ Applicant claims small entity status. See 37 CFR 1.27.

☐ A check or money order is enclosed to cover the filing fees

FILING FEE
AMOUNT (\$)

☒ The Commissioner is hereby authorized to charge filing
fees or credit any overpayment to Deposit Account Number:

14-1270

160.00

☐ Payment by credit card. Form PTO-2038 is attached.

The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.

☒ No.

☐ Yes, the name of the U.S. Government agency and the Government contract number are: _____

Respectfully submitted,

SIGNATURE

Date 8/11/03

REGISTRATION NO.: 48,027

(if appropriate)

TYPED or PRINTED NAME

AARON WAXLER

Docket Number: US030262

TELEPHONE

(914) 333-9608

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C., 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Alexandria, VA 22313-1450

In re Application of	Atty. Docket
GEORGE MARMAROPOULOS, ET.AL.	US030262
Serial No.	Group Art Unit
Filed: CONCURRENTLY	Ex.
Title: MAGNETIC ELECTRICAL INTERCONNECT	

Honorable Commissioner of Patents and Trademarks
Alexandria, VA 22313-1450

AUTHORIZATION PURSUANT TO 37 CFR §1.136(a) (3)
AND TO CHARGE DEPOSIT ACCOUNT

Sir:

The Commissioner is hereby requested and authorized to treat any concurrent or future reply in this application requiring a petition for extension of time for its timely submission, as incorporating a petition for extension of time for the appropriate length of time.

Please charge any additional fees which may now or in the future be required in this application, including extension of time fees, but excluding the issue fee unless explicitly requested to do so, and credit any overpayment, to Deposit Account No. 14-1270.

Respectfully submitted,

By Aaron Waxler
 Aaron Waxler, Reg. 48,027
 Patent Agent
 (914) 333-9608

MAGNETIC ELECTRICAL INTERCONNECT

FIELD OF THE INVENTION

The present invention relates generally to wearable electronics, and more particularly, to a magnetic electrical interconnect integrated for use in wearable electronic applications.

BACKGROUND OF THE INVENTION

Wearable electronics involves the integration of electronic items with fabric and garments. Examples of these are personal stereos, heart rate monitors, bio-feedback sensors, telephone headsets, data line connections, microprocessors, computerized components, etc.

Fabrics including conductive fibers are also commonly known in the art. Such fabrics include fibers interwoven with textile fibers to create circuits. Current can be selectively passed to an area on such fabric using a switch and a power source. Fig. 1 depicts a garment 2 that includes conductive fibers. Garment 2 has three current paths 3, 3', 3" that are made up of conductive fibers through which current can be passed from power source 4. Current paths can also be formed using other known techniques such as conductive ink. Garment 2 also includes a switch 5 that the wearer of the garment can select which current

path he or she chooses. For example, a user can attach a portable electronic device, such as a cellular telephone or portable radio, to garment 2 at clip 6. When the wearer sets switch 5 to power the electronic device, current passes from power source 4 through current path 3" to clip 6 and into the attached device. The conductive fibers that make up current paths 3, 3', and 3" can also be selected to have a high resistance. Consequently, they act as resistors and release electrical energy as heat. Current paths 3, 3', and 3" can be used to heat garment 2 in selected areas. However, these fabrics require additional electrical connections integrated into their basic functionality, such as at a button closure of a jacket.

WO 94/16587, entitled CLOSURE FOR A GARMENT OR THE LIKE, filed January 25, 1994, describes a closure for a garment intended to replace buttons and buttonholes with a magnet/ferromagnetic closure. This closure can be rotated to make or break a magnetic circuit and thereby open or close a garment. However, the magnetic circuit does not include means for forming an electrical connection.

WO 02/49465 A1, entitled PORTABLE ELECTRONIC EQUIPMENT, filed December 13, 2001, describes a clothing article with a network of transmission lines integrated into the textile material. The transmission lines can include a switch made from

a connector, such as a button. However, this disclosure only recites a button or snap connection that lacks the reliability of mechanical connection suitable to maintain a desirably consistent electrical connection. Further, both portions of the button/buttonhole or snap connection must be conductive to enable an electrical connection.

It is an object of the present invention to provide an improved fabric interconnect and method for controlling an attached electronic device which overcomes the limitations of the prior art.

It is another object of the present invention to provide such a fabric interconnect method that ensures mechanical and electrical connection.

SUMMARY OF THE INVENTION

In one aspect, an interconnect provides an improved fabric interconnect by including several portions. A first portion includes a magnet with a first magnetic direction and means for forming an electrical connection. A second portion includes means for forming an electrical connection when coupled with the first portion. The first and second portions form a mechanical connection and an electrical connection when connected.

In one embodiment, the first portion and second portion form a mechanical connection using magnetic attraction generated by the magnet.

In another embodiment, the second portion further comprises a magnet with a second magnetic direction.

In another embodiment, the electrical connection is aligned by the mechanical connection. In another embodiment, the electrical connection is aligned by the mechanical connection and a physical feature of the first and/or second portions.

In one embodiment, the first and second portions include means for mechanically connecting fabric materials. In another embodiment, the first and second portions receive electric current from a current supply source via fabric conductors contained within the fabric materials. In another embodiment, the first and second portions form an electrical circuit when mechanically connected. In another embodiment, the electrical circuit passes current from one location on a fabric material to another location on a fabric material. In another embodiment, the electrical circuit passes electrical signals from one location on a fabric material to a device.

In one embodiment, the means for forming an electrical connection includes a male connector or a female receptor. In another embodiment, the means for forming an electrical connection includes a surface contact. In another embodiment,

the means for forming an electrical connection of the first or second portion includes the magnet.

In another aspect, an interconnect includes several portions. A first portion includes an electromagnet and means for forming an electrical connection. The interconnect also includes means for supplying current to the electromagnet and a second portion including means for forming a electrical connection when coupled with the first portion. The first and second portions form a mechanical connection upon the electromagnet receiving current and further form an electrical connection when mechanically connected.

In one embodiment, the means for supplying current includes an electronic device. In another embodiment, the electronic device is a wearable electronic device. In another embodiment, the second portion further includes a magnet. In another embodiment, the magnet is an electromagnet. In another embodiment, the second portion includes a substance attracted by a magnet.

In another aspect, a method of controlling a device includes several steps. One step is coupling at least one interconnect in a series of interconnects, each including a first portion comprising a magnet with a first magnetic direction and means for forming an electrical connection and a second portion including means for forming a electrical

connection when coupled with the first portion, wherein the first and second portions form a mechanical connection and an electrical connection when connected. Another step is sensing the coupling of the at least one interconnect. Another step is controlling the device based upon the number of coupled or uncoupled interconnects in the series of interconnects.

In one embodiment, the sensing step further includes sensing when an electrical circuit is formed by the coupling step. In another embodiment, the controlling step includes incrementally controlling the device based upon the number of coupled or uncoupled interconnects.

In one embodiment, the device is a heating element contained in a garment, and the at least one interconnect is attached to the garment.

The invention provides many advantages that are evident from the following description, drawings, and claims.

BRIEF DESCRIPTION OF THE DRAWING

The invention may be more completely understood in reference to the following figures:

Fig. 1 depicts a prior art garment including conductive fibers;

Fig. 2 depicts a garment including magnetic electrical/mechanical interconnects;

Fig. 3 depicts an expanded view of portion A of Fig. 2;
Fig. 4 depicts a further embodiment of the interconnect;
Fig. 5 depicts an interconnect for securing a device to a garment;

Fig. 6 depicts a further embodiment of the interconnect;
Fig. 7 depicts a further embodiment of the interconnect;
Fig. 8 depicts a further embodiment of the interconnect;
Fig. 9 depicts a garment for controlling a device based on the number of connected interconnects.

DETAILED DESCRIPTION OF THE INVENTION

Fig. 2 depicts a garment 20 including magnetic interconnects 21 which serve to form mechanical connections to close garment 20 as well as to form electrical connections, for example, between power source 4 and a device 7. Interconnects 21 are formed by a first portion 22 and a second portion 23 which form a mechanical connection via magnetic attraction. First (22) and second (23) portions can be quickly coupled and decoupled and contain all the advantages of magnetic couplings, including ease of connection and simplicity of design.

Fig. 3 depicts an expanded view of portion A of Fig. 2. As shown in this view, interconnect 21 is formed by connecting first portion 22 and second portion 23. The mechanical coupling of interconnect 21 is generated by magnet 30 which is embedded

in first portion 22. Magnet 30 can be any type of substance which generates a magnetic field and thereby attracts another substance. Second portion 23 has at least one substance 31, either on its surface or contained within it, that is attracted by magnet 30. The magnetic force generated by magnet 30 attracting substance 31 must be at least mechanically strong enough to secure garment 20 from opening under reasonable force, but not so strong that a wearer of garment 20 cannot decouple the connection.

First 22 and second 23 portions are each electrically connected to current paths 3 that can be made up of conductive fibers through which current can be passed from power source 4. Current paths 3 can also be formed using any other technique known in the art, such as conductive ink. When mechanically connected, first 22 and second 23 portions form interconnect 21. Additionally, the surfaces of first 22 and second 23 portions contain electrical contacts that complete a circuit when the mechanical connection of interconnect 21 presses them together. Magnet 30, itself, can be the means for forming an electrical connection.

Fig. 4 depicts an alternate embodiment of the interconnect of Fig. 3. In this embodiment, both first 22 and second portions 23 contain magnets 30, 41, respectively. The magnets 30, 41 may contain opposite magnetic directions, thereby causing the

magnetic attraction and mechanical coupling of interconnect 21. Additionally, one or both of magnets 30, 41 can be an electromagnet powered by a source, such as power source 4. If, for example, first portion 22 contains an electromagnet, it would attract second portion 23 upon receiving current, thereby activating a magnetic field. Such a configuration is useful for automated interconnection of interconnects 21. A wearer of garment 20 could, for example, press a button and thereby initiate activation of selected electromagnets 30 contained in selected first portions 22. These first portions 22 would attract their respective second portions 23 and thus automatically both close the garment and form electrical connections.

Further, such interconnects including electromagnets could be used to secure devices to garment 20. For example, Fig. 5 shows a garment 20 including a pocket 50 in which a wearable electronic device 7 is held. The current path can be structured within garment 20 such that activating switch 55 and switching device 7 off would cut off power to an electromagnet contained in an interconnect 21 used to secure the pocket. Cutting off power to the electromagnet with eliminate its magnetic field and thereby release both the mechanical and electrical connection of interconnect 21. Thus, turning off device 7 will release the interconnect 21 that closes the pocket 50 in which device 7 is

held. Flap 54 of pocket 50 will not be mechanically held in place. Conversely, activating device 7 by switching switch 55 to on will supply current to the electromagnet that will generate a magnetic field. This will attract the other portion of interconnect 21 and form an electrical and mechanical connection automatically, thus securing device 7 to garment 20.

Fig. 6 shows an additional embodiment of the interconnect 21 where first portion 22 and second portion 23 contain electrical contact pads 51. When first portion 22 is mechanically connected to second portion 23, contact pads 51 are aligned to provide an electrical connection as well.

Fig. 7 shows an additional embodiment of the interconnect 21 where first portion 22 contains female sockets 62 and second portion 23 contains male connectors 61. When first portion 22 is mechanically connected to second portion 23, male connectors 61 are aligned with and inserted into female sockets 62, thereby forming an electrical connection.

Fig. 8 shows an additional embodiment of the interconnect 21 where first portion 22 contains indents 72 and second portion 23 contains extensions 71. When first portion 22 is mechanically connected to second portion 23, indents 72 and extensions 71 aligned first portion 22 and second portion 23 to provide an optimized mechanical and electrical connection. Any

physical feature may be used to assist in aligning first portion 22 and second portion 23 in forming interconnect 21.

Fig. 8 depicts garment 20 designed to control attached device 80. Device 80 includes sensor 81 which senses the coupling or decoupling of each interconnect 21. Sensor 81 detects when an interconnect 21 is coupled by detecting current flow through the electrical connection of interconnect 21. Device 80 is controlled based on the number of coupled or uncoupled interconnects 21 in the series of interconnects 21. Device 80 can be a heating device which will increase or decrease the heat it produces incrementally as the wearer couples or decouples individual interconnects 21.

The preceding expressions and examples are exemplary and are not intended to limit the scope of the claims which follow. Further, reference signs in the claims cannot be construed as limiting their scope.

What is claimed is:

1. An interconnect (21) comprising:

a first portion (22) comprising a magnet (30) with a first magnetic direction and means for forming an electrical connection; and

a second portion (23) comprising means for forming an electrical connection when coupled with the first portion,

wherein the first (22) and second (23) portions form a mechanical connection and an electrical connection when connected.

2. The interconnect (21) of Claim 1, wherein the first portion (22) and second (23) portion form a mechanical connection using magnetic attraction generated by the magnet (30).

3. The interconnect (21) of Claim 1, wherein the second portion (23) further comprises a magnet (41) with a second magnetic direction.

4. The interconnect (21) of Claim 2, wherein the electrical connection is aligned by the mechanical connection.

5. The interconnect (21) of Claim 4, wherein the electrical connection is aligned by the mechanical connection and a physical feature (71, 72) of the first (22) and/or second (23) portions.
6. The interconnect (21) of Claim 1, wherein the first (22) and second (23) portions comprise means for mechanically connecting fabric materials.
7. The interconnect (21) of Claim 6, wherein the first (22) and second (23) portions receive electric current from a current supply source (4) via fabric conductors (3) contained within the fabric materials.
8. The interconnect (21) of Claim 7, wherein the first (22) and second (23) portions form an electrical circuit when mechanically connected.
9. The interconnect (21) of Claim 8, wherein the electrical circuit passes current from one location on a fabric material to another location on a fabric material.

10. The interconnect (21) of Claim 8, wherein the electrical circuit passes electrical signals from one location on a fabric material to a device.

11. The interconnect (21) of Claim 1, wherein the means for forming an electrical connection comprises a male connector (61) or a female receptor (62).

12. The interconnect (21) of Claim 1, wherein the means for forming an electrical connection comprises a surface contact (51).

13. The interconnect (21) of Claim 1, wherein the means for forming an electrical connection of the first (22) or second (23) portion comprises the magnet (30).

14. An interconnect (21) comprising:

 a first portion (22) comprising an electromagnet (30) and means for forming an electrical connection;

 a means (4) for supplying current to the electromagnet (30); and

 a second portion (23) comprising means for forming an electrical connection when coupled with the first portion (22),

wherein the first (22) and second (23) portions form a mechanical connection upon the electromagnet (30) receiving current and further form an electrical connection when mechanically connected.

15. The interconnect (21) of Claim 14, wherein the means for supplying current (4) further comprises an electronic device (7).

16. The interconnect (21) of Claim 15, wherein the electronic device (7) is a wearable electronic device.

17. The interconnect (21) of Claim 14, wherein the second portion (23) further comprises a magnet (41).

18. The interconnect (21) of Claim 17, wherein the magnet (41) is an electromagnet.

19. The interconnect (21) of Claim 14, wherein the second portion (23) comprises a substance attracted by a magnet.

20. A method of controlling a device (7) comprising:

coupling at least one interconnect (21) in a series of interconnects (21), each comprising a first portion (22)

comprising a magnet (30) with a first magnetic direction and means for forming an electrical connection, and a second portion (23) comprising means for forming an electrical connection when coupled with the first portion (22), wherein the first (22) and second (23) portions form a mechanical connection and an electrical connection when connected;

sensing the coupling of the at least one interconnect (21);

controlling the device (7) based upon the number of coupled or uncoupled interconnects (21) in the series of interconnects (21).

21. The method of Claim 20, wherein the sensing step further comprises sensing when an electrical circuit is formed by the coupling step.

22. The method of Claim 21, wherein the controlling step further comprises incrementally controlling the device (7) based upon the number of coupled or uncoupled interconnects (21).

23. The method of Claim 21, wherein the device (7) is a heating element contained in a garment (20), and the at least one interconnect (21) is attached to the garment (20).

24. A garment (20) comprising:

an interconnect comprising a first portion (22) comprising a magnet (30) with a first magnetic direction and means for forming an electrical connection; and

a second portion (23) comprising means for forming an electrical connection when coupled with the first portion,

wherein the first (22) and second (23) portions form a mechanical connection and an electrical connection when connected.

ABSTRACT:

A garment 20 includes magnetic interconnects 21 which serve to form mechanical connections to close garment 20 as well as to form electrical connections, for example, between power source 4 and a device 7. Interconnects 21 are formed by a first portion 22 and a second portion 23 which form a mechanical connection via magnetic attraction. First 22 and second 23 portions can be quickly coupled and decoupled and contain all the advantages of magnetic couplings, including ease of connection and simplicity of design.

Fig. 2




Fig. 1
PRIOR ART





Fig. 2






Fig. 4







Fig. 5










Fig. 9

PATENT APPLICATION SERIAL NO. _____

U.S. DEPARTMENT OF COMMERCE
PATENT AND TRADEMARK OFFICE
FEE RECORD SHEET

08/13/2003 GWORDOF1 00000102 141270 60494135
01 FC:1005 160.00 DA

PTO-1556
(5/87)